

ImagePerfect™ 2810-202 is a clear, matt, polymeric laminate with an advanced acrylic permanent adhesive system. This material has been specifically designed for protecting digital prints.

IP 2810-202

ImagePerfect™ 2810-202 is a polymeric laminate incorporating specific polymeric, non-migrating plasticizers and UV stabilizers which ensure maximum light fastness and excellent outdoor durability. IP 2810-202 is intended for many flat applications, both interior and exterior, such as markings and decorations, window graphics and vehicle graphics. This laminate is recommended for use on IP 2553, IP 2553PA, IP 2554, IP 2556 and IP 2556PA.

Specifications	
DESCRIPTION	Polymeric laminate
COLOUR	Clear matt
THICKNESS	70µ
WEIGHT	N/A
ADHESIVE	Advanced acrylic, permanent
ADHESIVE STRENGTH	18N / 25mm (Finat TM 1/24h)
RELEASE PAPER	PE-coated silicone paper, 140g/m ²
TEMPERATURE RANGE	-30°C to +90°C
DURABILITY (UNPRINTED)	7 years
FLAME RETARDANCY	B1
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© September 2015 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

