

PRODUCT DATA SHEET

Product Code: SAFOV600FC1372

Issued April 2018

Indoor Floor Advertising

Frosty Clear Safari Overlaminates

Savvy marketers are placing advertisements on the floor directly in front of items being advertised to increase their product's presence and lift rate. Pressure-sensitive films for floors must withstand the wear and tear of heavy pedestrian traffic, floor buffers, chemicals, waxes, solvents, and wax strippers, while also meeting or exceeding industry accepted standards for slip resistance. The adhesive must hold the graphic in place, but also be cleanly removable after the promotion is over. Done right, floor graphics can be big ROI winners.

End-Use Applications:
Indoor Floor Advertising
Indoor Carpet Advertising
Counter Graphics

For more information on FLEXcon's pressure-sensitive film solutions for Indoor Floor Advertising, contact your local Sales Representative or our Product Branding Business Team at (508) 885-8370.

Product ID #: FLX066159



This image is an example of how FLEXcon products may be used

Product:

FLEXmark® OV6603BN

Benefits:

- 6.0 mil frosty clear safari overlaminating vinyl protects the printed graphic
- Safari finish enhances graphic images and prevents glare
- Permanent overlaminating pressure-sensitive acrylic adhesive bonds well to base film surface
- Adhesive offers excellent clarity and is designed to provide exceptional bond and excellent shear critical for durability under heavy foot traffic
- Smooth natural (tan) Kraft release liner helps ensure smooth flow-out of adhesive on the overlaminating film
- Approved overlaminate for floor graphic applications when used as a system with FLEXcon® FLEXmark® floor art™ 4652, 4652T, 6610, 6610T, 6640 (for carpets), 6640T (for carpets) base film - meets or exceeds industry accepted standard for non-slip performance UL 410

Must be used with one of the following base films:

- [FLEXmark floor art 4652](#)
- [FLEXmark floor art 4652T](#)
- [FLEXmark floor art 6610](#)
- [FLEXmark floor art 6610T](#)
- [FLEXmark floor art 6640](#)
- [FLEXmark floor art 6640T](#)

Additional Information:

[Application Instructions for Floors](#), [Application Instructions for Carpets](#)
[Warranty](#)



1 FLEXcon Industrial Park, Spencer, MA 01562-2642, Telephone (508) 885-8370 FAX (508) 885-8399 www.FLEXcon.com

• P: 1300 851 033 • F: 1300 658 889 • graphics@hvg.net.au • www.hvggraphics.com.au

PRODUCT DATA SHEET

Product Code: MOROV400HC1371

Issued November 2017

FLEXmark® OV6603BN

PRODUCT DATA	VALUE	TEST METHOD	
Physical Properties			
Thickness (Mils[microns])	Film	6.4 (163) +/- 10%	
	Adhesive	1.6-1.7 (41-43) +/- 0.1 (3)	
	Liner	3.0 (76) +/- 10%	
Dimensional Stability (%)	MD	0.75	
	TD	0.50	
Adhesion Properties			
Ultimate Peel from	Average	ASTM D 903 (Modified for 72 hour dwell time)	
	Oz/In		(N/m)
	Acrylic		61 (671)
	Glass		29 (319)
Stainless Steel	31 (341)		
Tack (gm/sq cm)	370		
Expected Exterior Life	Indoor use only		
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)		
Minimum Application Temperature	50°F (10°C)		
Storage Stability	Two years when stored at 70°F (21°C) and 50% relative humidity		

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by FLEXcon. All purchasers of FLEXcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of FLEXcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above. Last Modified On: 01/12/2018



1 FLEXcon Industrial Park, Spencer, MA 01562-2642, Telephone (508) 885-8370 FAX (508) 885-8399 www.FLEXcon.com

• P: 1300 851 033 • F: 1300 658 889 • graphics@hvg.net.au • www.hvggraphics.com.au