# **Mediapoint Gloss White BOPP**

#### **Quick Overview**

Stickler PP White TC 60 white gloss is a ultra white polypropylene top coated film designed for ultimate label application conformation on many difficult and contoured surfaces. Supplied with a clean crisp white finish for optimum screen and print tone resolution.

#### **Details**

Stickler PP White TC 60 white gloss is a ultra white polypropylene top coated film designed for ultimate label application conformation on many difficult and contoured surfaces. Supplied with a clean crisp white finish for optimum screen and print tone resolution.

## **Applications**

Recommended for labels where a durable face stock is required, eg Prime labels for body care, household chemicals, appliance, toys etc.

## **Technical Data**

#### **Face Material:**

| Properties | Test Method | Result     |
|------------|-------------|------------|
| Grammage   | ISO 536     | 54 g/m2    |
| Caliper    | ISO 534     | 60 microns |

## Adhesive:

AP901 General Purpose Permanent: Permanent pure acrylic adhesive designed for films. Featuring high cohesion, good clarity and very good performance on non-comparable substrates (PE,PP), ISEGA certified for direct food contact.

| Properties                 | Test Method                |
|----------------------------|----------------------------|
| Composition                | Water based acrylic        |
| Direct sunlight resistance | Excellent                  |
| Cohesion                   | High                       |
| Application temperature    | -5 degrees celsius         |
| Service temperature        | -40 to 120 degrees celcuis |
| Tack FTM 9                 | 8 N/Inch 2                 |
| Ultimate adhesion FTM 2    | 7 N/Inch                   |

#### Laminate:

| Laminate Shelf Life       | 24 months stored at 20°C/50% RH |
|---------------------------|---------------------------------|
| Typical laminate calendar | 134 ± 6 ums                     |
| Total weight              | 139 ± 6 RIT.PP-032              |

The technical specification includes our experience and know how in regards to the following:

a) The composition of our products

b) Their generic adhesive qualities normalised by means of the ISO procedure and regarding the international rule Finat generally accepted in this sector. Any reference to final use is subjected to our good knowledge an opinion and does not imply specific irrevocable guarantees for final use in end product labelling and packaging. Over and above these standards the product user is responsible for assessing, testing and ensuring the specific scope of the label in certain application by means of prior generic official approval.

# Backing

WG 1side siliconised supercalendered white glassine

Grammage 65gsm
Caliper 56 microns
Transparency > 40%

# **Important Note**

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.